




## PAR-P4LIR

4 Megapixel IP Plug & Play Outdoor Low Profile Camera  
Fixed Lens, 32' IR Range, PoE/DC12V, SD Card Slot

### Features

- 4 Megapixel (2592 x 1520) Resolution
- Fixed Lens
- H.265/H.264/MJPEG Compression
- True Day/Night
- True WDR 120dB
- EXIR Range up to 32'
- Audio Input/Output
- IP66 Weather Resistant
- 12VDC/PoE Operation
- ONVIF
- Free iOS & Android Apps, through the Paramount NVR, for Smart Phones & Tablets
- Free Central Management Software (CMS), through the Paramount NVR, to manage multiple units & sites from a single platform
- Free MAC client software available to manage your system from your Apple computer

### Mounting Options



**IPM-MINIJB2**  
Low Profile Camera Mount

Camera	
Image Sensor	1/3" Progressive Scan CMOS
Min. illumination	Color 0.05Lux; IR ON 0 Lux
True Day & Night	ICR
Shutter Speed	1/5-1/20000
Auto Iris	Fixed
Wide Dynamic Range	WDR>120dB
Digital Noise Reduction	2D/3D
Lens	2.8mm
FOV	90°
IR LED	1pcs
IR Range	32'
Image	
Video Compression	H.264/265, MJPEG
Bit Rate (CBR/VBR)	Main stream:500kb-12000kb ;Sub stream 100kb-6000kb
Audio Compression	G.711 ,RAW_PCM
Max.Resolution	2592*1520/2560*1440/20fps,2304*1296/30fps,1920x1080/30fps
Stream	Stream1 2592*1520/2560*1440/2304*1296/1920x1080 Stream 2 D1 to QVGA
Image Setting	Rotate Mode,Saturation,Brightness,Contrast,Sharpness
HLC	Yes
9:16 Corridor mode	Yes
DIS	Auto
ROI	Yes
Defog	Yes
Network	
Network Protocols:	HTTP,HTTPS, TCP/IP, UDP/IP, RTSP, DHCP, NTP, PPPoE, Unicast and Multicast supported.
Alarm Trigger	Motion Detection,Line Crossing,Tamper, Area Intrusion, Camera Move,Dwell,Multiple Dwell,Retrograde Detection,Object Left,Object Remove,Abnormal Speed,Illegal Parking,Network disconnect,Disk alarm
RTSP Video	Standard RFC2326, Support QuickTime / VLC Player.
Security	User security authentication, Reset, Hardware WatchDog
Web Language	English, Chinese,Polish, Italian, Portuguese, Spanish.(Sunell Brand)
System Compatibility	Onvif,CGI
Interface	
Ethernet	1 Ethernet (10/100 Base-T) RJ-45 Connector
Audio I/O	1ch Audio In&1ch Audio Out
BNC Output	Yes
Reset Button	Yes
Edge Storage	Micro SD/SDHC slot ,Max 128GB
General	
Power Supply	DC12V/POE
Power Consumption	2.5W(IR LED Off) 5W (IR LED On)
Operating Temperature	Starting Temperature: -30 °C~ 60 °C (-22 °F ~ 140 °F) Working Temperature:-40 °C ~ 60 °C (-40 °F ~ 140 °F)
Operating Humidity	0% - 90% RH
Ingress Protection	IP66
Approvals	CE / FCC
Product Dimensions	Ø3.93 x 2.08 inches (Ø100x53mm)
Product Weight	0.88 lbs (400g)

### Ordering Information

**PAR-P4LIR28:** Low Profile Camera, 2.8mm

*\*IRs are for minimal illumination and not complete darkness. Best when used with some ambient light.  
InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.*