

HED402 Auto Drain

Purpose

This product often applies to the low places of auto-remove piping, frozen type air drying machine, oil separator, air storage tank and the bottom of various air filters. It can be installed in the places which are not convenient for manual discharge of sewage, such as high, low, narrow places. Especially, it can be installed in the places with large consumption of air or frequent drain times, to prevent the compressed air to be re-polluted by condensed water resulting from the neglect of manual drain.


Features

Auto drain/ Zero pressure drain/ Manual drain/ The water cup with metal bowl guard.

Attention

The drainer should be installed vertically and the port should face down, when using.

Main Dimensions (mm)



Model	HED402-02	HED402-03	HED402-04
Working medium	Compressed air		
Working pressure (MPa)	0.15-1.0		
Guaranteed pressure resistance (MPa)	1.5		
Working temperature (°C)	5-60		
Port size	G1/4	G3/8	G1/2
Drain port size	G1/8		
Drain status	Normal open		

ZDFS Auto Discharger

Application Range

This product is installed at the bottom of water cups for auto dischargers, air filters and air filter regulators to discharge the condensed water gathered in the water cup.

Technical requirements

Working medium, compressed air
Working temperature: 5-60°C
Working pressure: 1.5-10Bar

Features

Auto drain/ Zero pressure drain/ Manual drain

Attention

The drainer should be installed vertically and the port should face down, when using.

Main Dimensions (mm)

