



Accessories

Type	Description	Cyl. bore Ø mm	Weight kg	Order code
Flexo coupling 	Flexo coupling for articulated mounting of piston rod. Flexo coupling is intended to take up axial angle errors within a range of $\pm 4^\circ$.	32	0,21	P1C-4KRF
		40	0,22	P1C-4LRF
		50	0,67	P1C-4MRF
		63	0,67	P1C-4MRF
	Material Flexocoupling, nut: Zinc-plated steel Socket: Hardened steel	80	0,72	P1C-4PRF
		100	0,72	P1C-4PRF
		125	1,80	P1C-4RRF

Supplied complete with galvanized adjustment nut.

Cyl. bore mm	B min mm	B max mm	DL	EH	EI	EK	EL	EN	EO	EP	EQ	ER	M	Z
mm	mm	mm		mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	
32	36	43	M10x1,25	20	23	70	31	12	30	30	19	30	5	4°
40	37	43	M12x1,25	23	23	67	31	12	30	30	19	30	6	4°
50	53	61	M16x1,5	40	32	112	45	19	41	41	30	41	8	4°
63	53	61	M16x1,5	40	32	112	45	19	41	41	30	41	8	4°
80	57	67	M20x1,5	39	42	122	56	19	41	41	30	41	10	4°
100	57	67	M20x1,5	39	42	122	56	19	41	41	30	41	10	4°
125	75,5	89	M27x2	48	48	145	60	24	55	55	32	55	13,5	4°



Nut 	Intended for fixed mounting of accessories to the piston rod. Material: Galvanized steel (Cylinders supplied with galvanized nut)	32	0,007	9128985601
		40	0,010	0261109910
		50	0,021	9128985603
		63	0,021	9128985603
		80	0,040	0261109911
		100	0,040	0261109911
		125	0,100	0261109912

Stainless steel nut 	Intended for fixed mounting of accessories to the piston rod. Material: Stainless steel (Cylinders supplied with galvanized nut)	32	0,007	9126725404
		40	0,010	9126725405
		50	0,021	9126725406
		63	0,021	9126725406
		80	0,040	0261109921
		100	0,040	0261109921
		125	0,100	0261109922

Acid-proof nut 	Intended for fixed mounting of accessories to the piston rod. Material: Acid-proof steel (Cylinders with acid-proof piston rod are supplied with nut of acid-proof steel)	32	0,007	0261109919
		40	0,010	0261109920
		50	0,021	0261109917
		63	0,021	0261109917
		80	0,040	0261109916
		100	0,040	0261109916
		125	0,100	0261109918

According to DIN 439 B

Cyl. bore mm	A mm	B mm	C
32	17	5	M10x1,25
40	19	6	M12x1,25
50	24	8	M16x1,5
63	24	8	M16x1,5
80	30	10	M20x1,5
100	30	10	M20x1,5
125	41	13,5	M27x2

