

Accessories
TS 32X15 2M/ST/ZN

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

**Building installation wiring**

For building installations, we offer a complete system that revolves around the 10×3 copper rail and comprises perfectly coordinated components: from installation terminal blocks, neutral conductor terminal blocks and distribution terminal blocks to comprehensive accessories such as busbars and busbar holders.

General ordering data

Type	TS 32X15 2M/ST/ZN
Order No.	0122800000
Version	Mounting rail, TS 32, without slot, Steel, galvanized, chromium-plated, 2000 mm
GTIN (EAN)	4008190066307
Qty.	2 m

Data sheet

Accessories TS 32X15 2M/ST/ZN

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

Length	2,000 mm	Length (inches)	78.74 inch
Width	32 mm	Width (inches)	1.26 inch
Height	33 mm	Height (inches)	1.299 inch
Depth	15 mm	Depth (inches)	0.591 inch
Net weight	720 g		

Material data

Material	Steel	Surface finish	galvanized, chromium-plated
Colour	Silver		

System specifications

Version	without slot	Mounting rail	TS 32
---------	--------------	---------------	-------

Additional technical data

Installation advice	Direct mounting	Type of mounting	Screwed
---------------------	-----------------	------------------	---------

Mounting rail

Short circuit strength corresponds to E-Cu wire	35 mm ²	Thickness	1.5 mm
---	--------------------	-----------	--------

Rating data

Standards	DIN EN 60715
-----------	--------------

Classifications

ETIM 3.0	EC001285	ETIM 4.0	EC001285
ETIM 5.0	EC001285	ETIM 6.0	EC001285
UNSPSC	30-21-18-01	eClass 5.1	27-14-06-04
eClass 6.2	27-14-11-43	eClass 7.1	27-14-11-43
eClass 8.1	27-14-11-43	eClass 9.0	27-14-11-43
eClass 9.1	27-40-06-02		

Product information

Descriptive text ordering data	TS 32X15 2M/AL/BK: max. permitted rated current for PEN function = 192 A
--------------------------------	--

Approvals

ROHS	Conform
------	---------

Downloads

Brochure/Catalogue	CAT 1 TERM 16/17 EN
Engineering Data	EPLAN, WSCAD, Zuken E3.S
Engineering Data	0122800000_06081_TS_32X15_2M-ST-ZN_STP.stp