

CableLine CLI C 02-3 GE/SW R MP

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



CLI C conductor markers are mounted on unconnected conductors. Four different sizes are available for labelling conductor cross-sections from 0.5 mm² to max. 70 mm². The markers are already printed and ready for use. Individual labelling is possible by combining the individual markers.

- Closed markers, reliable and for mounting on unconnected cables
- A special flexible bellow profile ensures a wide application range
- Fast and easy to fit – with minimal effort
- Corresponding accessories make labelling easy
- Permanent, high-quality labelling
- High contrast for optimum legibility

General ordering data

| | |
|------------|--|
| Type | CLI C 02-3 GE/SW R MP |
| Order No. | 0252111671 |
| Version | CableLine, Conductor and cable markers, 1 - 3 mm, 3 x 3.4 mm, Yellow |
| GTIN (EAN) | 4008190117177 |
| Qty. | 200 pc(s). |

CableLine
CLI C 02-3 GE/SW R MP

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data**Dimensions and weights**

| | | | |
|------------|--------|-----------------|------------|
| Width | 3.4 mm | Width (inches) | 0.134 inch |
| Height | 3 mm | Height (inches) | 0.118 inch |
| Depth | 3.5 mm | Depth (inches) | 0.138 inch |
| Net weight | 0.04 g | | |

General data

| | | | |
|-----------------------------|----------------------------|--|--------------------|
| Colour | Yellow | Colour of printing | Black |
| Material | PVC, soft, without Cadmium | Material colour according to resistance code | 4 |
| Operating temperature range | -30...80 °C | Orientation of print | horizontal |
| Printed characters | Upper-case letters | Printing | R |
| Printing method | Laser print | Recommended industries | Process, Machinery |
| Type of printing | Standard | UL 94 flammability rating | V-0 |
| Version | MultiPack | Width | 3.4 mm |

Conductor and cable markers

| | | | |
|-------------------------------|---------------------|-------------------------------|---------------------|
| Conductor O.D. | 1 - 3 mm | Conductor O.D., max. | 3 mm |
| Conductor O.D., min. | 1 mm | Conductor cross-section, max. | 1.5 mm ² |
| Conductor cross-section, min. | 0.5 mm ² | Halogen | Yes |

Classifications

| | | | |
|------------|-------------|------------|-------------|
| ETIM 3.0 | EC001530 | ETIM 4.0 | EC001288 |
| ETIM 5.0 | EC001530 | ETIM 6.0 | EC001530 |
| UNSPSC | 44-12-17-08 | eClass 5.1 | 27-14-91-03 |
| eClass 6.2 | 27-40-04-01 | eClass 7.1 | 27-14-91-29 |
| eClass 8.1 | 27-14-91-03 | eClass 9.0 | 27-14-07-08 |
| eClass 9.1 | 27-40-04-01 | | |

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Downloads

| | |
|------------------|------------------------------|
| Engineering Data | EPLAN, WSCAD |
|------------------|------------------------------|

Data sheet

CableLine
CLI C 02-3 GE/SW R MP

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings



Similar to illustration