

**CableLine  
CLI C 1-6 GE/SW L3 MP**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



CLI C conductor markers are mounted on unconnected conductors. Four different sizes are available for labelling conductor cross-sections from 0.5 mm<sup>2</sup> to max. 70 mm<sup>2</sup>. The markers are already printed and ready for use. Individual labelling is possible by combining the individual markers.

- Closed markers, reliable and for mounting on unconnected cables
- A special flexible bellow profile ensures a wide application range
- Fast and easy to fit – with minimal effort
- Corresponding accessories make labelling easy
- Permanent, high-quality labelling
- High contrast for optimum legibility

**General ordering data**

|            |  |
|------------|--|
| Type       | CLI C 1-6 GE/SW L3 MP  |
| Order No.  | <a href="#">0252711730</a>   |
| Version    | CableLine, Conductor and cable markers, 3 - 5 mm, 6 x 4.2 mm, Yellow |
| GTIN (EAN) | 4008190078126  |
| Qty.       | 100 pc(s).   |

## CableLine CLI C 1-6 GE/SW L3 MP

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

## Technical data

### Dimensions and weights

|            |        |                 |            |
|------------|--------|-----------------|------------|
| Width      | 4.2 mm | Width (inches)  | 0.165 inch |
| Height     | 6 mm   | Height (inches) | 0.236 inch |
| Depth      | 5 mm   | Depth (inches)  | 0.197 inch |
| Net weight | 0.11 g |                 |            |

### General data

|  |                    |                             |                            |
|--|--------------------|-----------------------------|----------------------------|
| Colour                                       | Yellow             | Colour of printing          | Black                      |
| Insulation cross-section, max.               | 5 mm               | Material                    | PVC, soft, without Cadmium |
| Material colour according to resistance code | 4                  | Operating temperature range | -30...80 °C                |
| Orientation of print                         | horizontal         | Printed characters          | Mixed characters           |
| Printing                                     | L3                 | Printing method             | Laser print                |
| Recommended industries                       | Process, Machinery | Type of printing            | Standard                   |
| UL 94 flammability rating                    | V-0                | Version                     | MultiPack                  |
| Width  | 4.2 mm             |                             |                            |

### Conductor and cable markers

|                               |                     |                               |                   |
|-------------------------------|---------------------|-------------------------------|-------------------|
| Conductor O.D.                | 3 - 5 mm            | Conductor O.D., max.          | 5 mm              |
| Conductor O.D., min.          | 3 mm                | Conductor cross-section, max. | 4 mm <sup>2</sup> |
| Conductor cross-section, min. | 1.5 mm <sup>2</sup> | Halogen                       | Yes               |

### Classifications

|            |             |            |             |
|------------|-------------|------------|-------------|
| ETIM 3.0   | EC001530    | ETIM 4.0   | EC001288    |
| ETIM 5.0   | EC001530    | ETIM 6.0   | EC001530    |
| UNSPSC     | 44-12-17-08 | eClass 5.1 | 27-14-91-03 |
| eClass 6.2 | 27-40-04-01 | eClass 7.1 | 27-14-91-29 |
| eClass 8.1 | 27-14-91-03 | eClass 9.0 | 27-14-07-08 |
| eClass 9.1 | 27-40-04-01 |            |             |

### Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

### Downloads

|                  |                              |
|------------------|------------------------------|
| Engineering Data | <a href="#">EPLAN, WSCAD</a> |
|------------------|------------------------------|

**Data sheet**

**CableLine  
CLI C 1-6 GE/SW L3 MP**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**



Similar to illustration