

SAK Series
QS 2/8/4**Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com**Current and voltage transformer wiring**

Our test disconnect terminal blocks featuring spring and screw connection technology allow you to create all the important converter circuits for measuring current, voltage and power in a safe and sophisticated way.

General ordering data

| | |
|------------|---|
| Type | QS 2/8/4 |
| Order No. | 0270960000 |
| Version | SAK Series, Short-circuit plug, For the terminals, No. of poles: 2 |
| GTIN (EAN) | 4008190077006 |
| Qty. | 20 pc(s). |

**SAK Series
QS 2/8/4**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data**Dimensions and weights**

| | | | |
|------------|---------|-----------------|------------|
| Width | 12 mm | Width (inches) | 0.472 inch |
| Height | 16 mm | Height (inches) | 0.63 inch |
| Depth | 34.5 mm | Depth (inches) | 1.358 inch |
| Net weight | 6.104 g | | |

Material data

| | |
|--------|-------|
| Colour | Beige |
|--------|-------|

System specifications

| | | | |
|---------|-------------------|---------------|------|
| Version | For the terminals | Mounting rail | none |
|---------|-------------------|---------------|------|

Additional technical data

| | | | |
|--------------------------|---------|---------------------|-----------------|
| Explosion-tested version | No | Installation advice | Direct mounting |
| Type of fixing | Plugged | | |

Dimensions

| | |
|-----------------|------|
| Pitch in mm (P) | 8 mm |
|-----------------|------|

Rating data

| | |
|---------------|------|
| Rated current | 44 A |
|---------------|------|

Classifications

| | | | |
|------------|-------------|------------|-------------|
| ETIM 3.0 | EC000489 | ETIM 4.0 | EC000489 |
| ETIM 5.0 | EC000489 | ETIM 6.0 | EC000489 |
| UNSPSC | 30-21-18-01 | eClass 5.1 | 27-14-11-40 |
| eClass 6.2 | 27-14-11-40 | eClass 7.1 | 27-14-11-40 |
| eClass 8.1 | 27-14-11-40 | eClass 9.0 | 27-14-11-40 |
| eClass 9.1 | 27-14-11-40 | | |

Product information

| | |
|---------------------------------|-------------------------------------|
| Descriptive text technical data | Current-carrying capacity max. 44 A |
|---------------------------------|-------------------------------------|

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Downloads

| | |
|--------------------|--|
| Brochure/Catalogue | CAT 1 TERM 16/17 EN |
| Engineering Data | EPLAN, WSCAD, Zuken E3.S |