

Accessories

TS 35X7.5 2M/AL/BK

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com



Building installation wiring

For building installations, we offer a complete system that revolves around the 10×3 copper rail and comprises perfectly coordinated components: from installation terminal blocks, neutral conductor terminal blocks and distribution terminal blocks to comprehensive accessories such as busbars and busbar holders.

General ordering data

Type	TS 35X7.5 2M/AL/BK
Order No.	0330800000
Version	Mounting rail, TS 35, TS 35 x 7.5, without slot, Aluminium, untreated, 2000 mm
GTIN (EAN)	4008190100650
Qty.	2 m

**Accessories
TS 35X7.5 2M/AL/BK**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data
Dimensions and weights

Length	2,000 mm	Length (inches)	78.74 inch
Width	35 mm	Width (inches)	1.378 inch
Height	35 mm	Height (inches)	1.378 inch
Depth	7.5 mm	Depth (inches)	0.295 inch
Net weight	108.2 g		

Material data

Material	Aluminium	Surface finish	untreated
Colour	Silver		

System specifications

Version	without slot	Mounting rail	TS 35, TS 35 x 7.5
---------	--------------	---------------	--------------------

Additional technical data

Installation advice	Direct mounting	Type of mounting	Screwed
---------------------	-----------------	------------------	---------

Mounting rail

Max. permitted rated current for PEN function	125 A	Short circuit strength corresponds to E-Cu wire	35 mm ²
Thickness	1 mm		

Rating data

Standards	DIN EN 60715
-----------	--------------

Classifications

ETIM 3.0	EC001285	ETIM 4.0	EC001285
ETIM 5.0	EC001285	ETIM 6.0	EC001285
UNSPSC	30-21-18-01	eClass 5.1	27-14-06-04
eClass 6.2	27-14-11-43	eClass 7.1	27-14-11-43
eClass 8.1	27-14-11-43	eClass 9.0	27-14-11-43
eClass 9.1	27-40-06-02		

Product information

Descriptive text ordering data	TS 35X7.5 2M/AL/BK: max. permitted rated current for PEN function = 125 A
--------------------------------	---

Approvals

ROHS	Conform
------	---------

Downloads

Brochure/Catalogue	CAT 1 TERM 16/17 EN
Engineering Data	EPLAN, WSCAD, Zuken E3.S