

**SAK Series**  
**Q 4 AKZ1.5**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Klippon® Connect with clamping yoke Technology**

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

**General ordering data**

|            |   |
|------------|---|
| Type       | Q 4 AKZ1.5  |
| Order No.  | <a href="#">0368400000</a>  |
| Version    | SAK Series, Cross-connector, for cross-connection link, No. of poles: 4 |
| GTIN (EAN) | 4008190153892   |
| Qty.       | 50 pc(s).   |

## Data sheet

### SAK Series Q 4 AKZ1.5

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technical data

### Dimensions and weights

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Width      | 19.3 mm | Width (inches)  | 0.76 inch  |
| Height     | 4 mm    | Height (inches) | 0.157 inch |
| Depth      | 11 mm   | Depth (inches)  | 0.433 inch |
| Net weight | 3.36 g  |                 |            |

### Material data

|          |      |        |      |
|----------|------|--------|------|
| Material | CuSn | Colour | Grey |
|----------|------|--------|------|

### System specifications

|               |                           |                                     |              |
|---------------|---------------------------|-------------------------------------|--------------|
| Version       | for cross-connection link | Tightening torque (cross-connector) | 0.4...0.8 Nm |
| Mounting rail | none                      |                                     |              |

### Additional technical data

|                          |         |                     |                 |
|--------------------------|---------|---------------------|-----------------|
| Explosion-tested version | No      | Installation advice | Direct mounting |
| Type of fixing           | Screwed |                     |                 |

### Dimensions

|                 |        |
|-----------------|--------|
| Pitch in mm (P) | 5.1 mm |
|-----------------|--------|

### Rating data

|               |      |
|---------------|------|
| Rated current | 24 A |
|---------------|------|

### Classifications

|            |             |            |             |
|------------|-------------|------------|-------------|
| ETIM 3.0   | EC000489    | ETIM 4.0   | EC000489    |
| ETIM 5.0   | EC000489    | ETIM 6.0   | EC000489    |
| UNSPSC     | 30-21-18-01 | eClass 5.1 | 27-14-11-40 |
| eClass 6.2 | 27-14-11-40 | eClass 7.1 | 27-14-11-40 |
| eClass 8.1 | 27-14-11-40 | eClass 9.0 | 27-14-11-40 |
| eClass 9.1 | 27-14-11-40 |            |             |

### Product information

|                                 |   |
|---------------------------------|---|
| Descriptive text technical data | 24 A for max. conductor size of 2.5 mm <sup>2</sup> |
|---------------------------------|---|

### Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

### Downloads

|                    |   |
|--------------------|---|
| Brochure/Catalogue | <a href="#">CAT 1 TERM 16/17 EN</a>   |
| Engineering Data   | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>  |
| Engineering Data   | <a href="#">0368400000_04444_Q_4_AKZ1.5_STP.stp</a><br><a href="#">04444_Q_4_AKZ1.5_DXF.dxf</a> |