

**Accessories  
G 20/6.30A/F**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Klippon® Connect with clamping yoke Technology**

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

**General ordering data**

Type	G 20/6.30A/F
Order No.	<a href="#">0431400000</a>
Version	Active components, Fuse
GTIN (EAN)	4008190086053
Qty.	10 pc(s).

## Accessories G 20/6.30A/F

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technical data

### Dimensions and weights

Width	5 mm	Width (inches)	0.197 inch
Height	20 mm	Height (inches)	0.787 inch
Depth	5 mm	Depth (inches)	0.197 inch
Net weight	1.1 g		

### Material data

Colour	Light Grey
--------	------------

### System specifications

Version	Fuse accessories
---------	------------------

### Fuse cartridges

Cartridge fuse	G-Si. 5 x 20	Characteristics	quick-acting
Colour	Light Grey	Current	6.3 A
Melting integral	32 A <sup>2</sup> s	Power output (@ 1.5 In)	2.6 W
Rated breaking capacity	1.5 kA	Version	Fuse accessories
Voltage drop	130 mV		

### Rating data

Rated voltage	250 V	Rated current	6.3 A
---------------	-------	---------------	-------

### Classifications

ETIM 3.0	EC000035	ETIM 4.0	EC000035
ETIM 5.0	EC000035	ETIM 6.0	EC000035
UNSPSC	30-21-18-14	eClass 5.1	27-14-20-07
eClass 6.2	27-14-20-07	eClass 7.1	27-14-20-90
eClass 8.1	27-14-20-90	eClass 9.0	27-14-20-90
eClass 9.1	27-14-20-01		

### Product information

Descriptive text ordering data	(M) = medium time-lag; (F) = quick-acting
Descriptive text technical data	<ol style="list-style-type: none"> <li>1) The company SIBA supplies G-type fuse cartridges 5 x 25 with indicator, also available in marine engineering version for 450 V~.</li> <li>2) Fuse cartridges 5 x 30 (500 V~) for SAKS 3 are available from the company WICKMANN.</li> <li>3) The company LINDNER supplies Neozed fuse cartridges, also available in marine engineering version for 440 V~.</li> <li>4) Fuse cartridges with the dimensions 1" x 1/4" (25.4 x 6.35 mm) and 13/32" x 1 1/2" (10.3 x 38.1 mm) are not included in the product range.</li> <li>5) Only for SAKS 1 and SAKS 7.</li> </ol>

### Approvals

ROHS	Conform
------	---------

### Downloads

Brochure/Catalogue	<a href="#">CAT 1 TERM 16/17 EN</a>
Engineering Data	<a href="#">WSCAD</a>