

**SAK Series  
HP 3 ADP3**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Building installation wiring**

For building installations, we offer a complete system that revolves around the 10×3 copper rail and comprises perfectly coordinated components: from installation terminal blocks, neutral conductor terminal blocks and distribution terminal blocks to comprehensive accessories such as busbars and busbar holders.

**General ordering data**

|            |                                       |
|------------|---------------------------------------|
| Type       | HP 3 ADP3                             |
| Order No.  | <a href="#">0485760000</a>            |
| Version    | SAK Series, Fixing plate, Beige, 3 mm |
| GTIN (EAN) | 4008190030254                         |
| Qty.       | 20 pc(s).                             |

**SAK Series  
HP 3 ADP3**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data****Dimensions and weights**

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Width      | 3 mm    | Width (inches)  | 0.118 inch |
| Height     | 82 mm   | Height (inches) | 3.228 inch |
| Depth      | 86.5 mm | Depth (inches)  | 3.406 inch |
| Net weight | 8.104 g |                 |            |

**Temperatures**

|                                  |        |                                  |        |
|----------------------------------|--------|----------------------------------|--------|
| Continuous operating temp., min. | -50 °C | Continuous operating temp., max. | 100 °C |
|----------------------------------|--------|----------------------------------|--------|

**Material data**

|                           |       |        |       |
|---------------------------|-------|--------|-------|
| Material                  | PA 66 | Colour | Beige |
| UL 94 flammability rating | V-2   |        |       |

**System specifications**

|         |                            |               |      |
|---------|----------------------------|---------------|------|
| Version | End and intermediate plate | Mounting rail | none |
|---------|----------------------------|---------------|------|

**Additional technical data**

|                     |                 |         |     |
|---------------------|-----------------|---------|-----|
| Installation advice | Direct mounting | Snap-on | Yes |
|---------------------|-----------------|---------|-----|

**Dimensions**

|                 |         |
|-----------------|---------|
| Mounting offset | 26.5 mm |
|-----------------|---------|

**Classifications**

|            |             |            |             |
|------------|-------------|------------|-------------|
| ETIM 3.0   | EC000886    | ETIM 4.0   | EC000886    |
| ETIM 5.0   | EC000886    | ETIM 6.0   | EC000886    |
| UNSPSC     | 30-21-18-27 | eClass 5.1 | 27-14-11-33 |
| eClass 6.2 | 27-14-11-33 | eClass 7.1 | 27-14-11-33 |
| eClass 8.1 | 27-14-11-33 | eClass 9.0 | 27-14-11-33 |
| eClass 9.1 | 27-14-11-33 |            |             |

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                    |                                     |
|--------------------|-------------------------------------|
| Brochure/Catalogue | <a href="#">CAT 1 TERM 16/17 EN</a> |
| Engineering Data   | <a href="#">EPLAN, WSCAD</a>        |