

CableLine CLI O 20-3 GE/SW 0 MP

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



CLI O conductor markers are fitted to connected conductors, and are therefore suitable for updating existing systems. Without problems, three different sizes can be used for marking conductor cross-sections from 0.4 mm² to max. 4.0 mm². The shape and design guarantee secure and permanent attachment of the individually combinable markers.

Advantages:

- Open markers for connected conductors
- Marker version with anti-rotation safeguard for secure combination marking
- Perfect for any supplementary labelling
- Extremely low space requirements
- Rapid clip-on attachment saves time

General ordering data

| | |
|------------|----------------------------------------------------------------------|
| Type | CLI O 20-3 GE/SW 0 MP |
| Order No. | 0648101502 |
| Version | CableLine, Conductor and cable markers, 3 - 4 mm, 3 x 5.5 mm, Yellow |
| GTIN (EAN) | 4008190063009 |
| Qty. | 200 pc(s). |

CableLine
CLI O 20-3 GE/SW 0 MP

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data**Dimensions and weights**

| | | | |
|------------|---------|-----------------|------------|
| Width | 5.5 mm | Width (inches) | 0.217 inch |
| Height | 3 mm | Height (inches) | 0.118 inch |
| Depth | 5 mm | Depth (inches) | 0.197 inch |
| Net weight | 0.045 g | | |

General data

| | | | |
|-----------------------------|----------------------------|----------------------------------------------|--------------------|
| Colour | Yellow | Colour of printing | Black |
| Material | PVC, soft, without Cadmium | Material colour according to resistance code | 4 |
| Operating temperature range | -30...80 °C | Orientation of print | horizontal |
| Printed characters | Numbers | Printing | 0 |
| Printing method | Laser print | Recommended industries | Process, Machinery |
| Type of printing | Standard | UL 94 flammability rating | V-0 |
| Version | MultiPack | Width | 5.5 mm |

Conductor and cable markers

| | | | |
|-------------------------------|---------------------|-------------------------------|-------------------|
| Conductor O.D. | 3 - 4 mm | Conductor O.D., max. | 4 mm |
| Conductor O.D., min. | 3 mm | Conductor cross-section, max. | 3 mm ² |
| Conductor cross-section, min. | 1.5 mm ² | Halogen | Yes |

Classifications

| | | | |
|------------|-------------|------------|-------------|
| ETIM 3.0 | EC001530 | ETIM 4.0 | EC001288 |
| ETIM 5.0 | EC001530 | ETIM 6.0 | EC001530 |
| UNSPSC | 44-12-17-08 | eClass 5.1 | 27-14-91-03 |
| eClass 6.2 | 27-40-04-01 | eClass 7.1 | 27-14-91-29 |
| eClass 8.1 | 27-14-91-03 | eClass 9.0 | 27-14-91-03 |
| eClass 9.1 | 27-40-04-01 | | |

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Downloads

| | |
|------------------|------------------------------|
| Engineering Data | EPLAN, WSCAD |
|------------------|------------------------------|

Data sheet

CableLine
CLI O 20-3 GE/SW 0 MP

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings



Similar to illustration